P/N MAC-49999076

High-Pressure Breathing Air Compressor – 100 L/min, 330 bar

Compresor de aire respirable de alta presión – 100 L/min, 330 bar

Portable, air-cooled high-pressure compressor for charging breathing-air cylinders such as SCBA (300 bar) and EEBD (210 bar) cylinders on board. Driven by a 3 kW three-phase electric motor in a protective tubular frame with guarded cooling fan.

KEY FEATURES

- Free air output 100 L/min
- Maximum working pressure 330 bar — suits 300 bar SCBA cylinders
- 3 kW three-phase electric drive, 220 / 380 V, 50 / 60 Hz
- Air-cooled; guarded cooling fan
- Tubular carrying frame for portable use

PRODUCT



TECHNICAL SPECIFICATIONS

Part number	MAC-49999076
Type	High-pressure breathing-air compressor
Free air output	100 L/min
Max. working pressure	330 bar
Driving power	3 kW
Drive	Three-phase electric motor
Power supply	220 V / 380 V; 50 / 60 Hz
Cooling	Air cooled
Fill adapters	MRA-30709003 (G5/8, SCBA); MRA-30805003 (M22×1.5) / MRA-30805005 (G5/8, EEBD)

330 BAR | 100 L/MIN | 3 KW | 3-PHASE

Genuine OEM equivalent available on request. Breathing-air quality standard, filtration and fill-hose configuration to be confirmed with the quotation. Illustration for reference; appearance may vary.