P/N MBL-30602009

Lifebuoy Self-Igniting Light – Explosion-Proof, Ex ia IIC T4

Luz autoencendible para aro salvavidas – antiexplosiva, Ex ia IIC T4

Intrinsically safe self-igniting lifebuoy light for tankers, gas carriers and offshore installations. LED light source, two alkaline LR20 (D) batteries, IP68. Switches on when upright, off when stowed inverted.

KEY FEATURES

- Intrinsically safe: Ex ia IIC T4
- IP68 protection
- LED light source; 2 × alkaline LR20 (D)
- Self-igniting when upright; off when stowed inverted

PRODUCT



TECHNICAL SPECIFICATIONS

Part number	MBL-30602009
Type	Lifebuoy self-igniting light, intrinsically safe
Explosion protection	Ex ia IIC T4
Ex standards	IEC 60079-0; IEC 60079-11
Protection class	IP68
Light source	LED, white, flashing
Luminous intensity	≥2 cd per OEM data
Operating time	≥2 h per OEM data
Battery	2 × alkaline LR20 (D)
Size / weight	Ø100 × 295 mm / 700 g
Approval	EU MED per OEM data; certificate to be confirmed
Alternate	MBL-30602008 — CCS version per OEM data

EX IA IIC T4 | IP68 | IEC 60079-11 | SOLAS 1974

Genuine OEM equivalent available on request. For hazardous areas. Change batteries only in a safe area. For use with lifebuoys ≥4 kg. Illustration for reference; appearance may vary.