P/N MCY-20304040

# SCBA Air Cylinder – 6 L Alloy Steel, 300 bar

*Cilindro de aire para ERA – acero aleado 6 L, 300 bar*

Alloy-steel breathing-air cylinder for 300 bar positive-pressure SCBA sets used in the SOLAS fire-fighter's outfit. Spare or replacement cylinder for the 6 L SCBA range (MSC-30703001 / -30703004). Internal neck thread M22×1.5; a G5/8 version is available.

## KEY FEATURES

- Robust alloy-steel construction
- 6 L water capacity, 300 bar working pressure
- Stores 1,800 L of breathing air when fully charged
- M22×1.5 internal neck thread (G5/8 version: MCY-20304049)
- Fits the 6 L 300 bar SCBA range; cylinders are interchangeable within the approved SCBA

## PRODUCT



## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Part number** | MCY-20304040 |
| **Type** | SCBA breathing-air cylinder |
| **Material** | Alloy steel |
| **Water capacity** | 6 L |
| **Working pressure** | 300 bar |
| **Air capacity** | 1,800 L (at 300 bar) |
| **Neck thread** | M22×1.5 (internal) |
| **Cylinder approval** | TPED (transportable pressure equipment directive) |
| **Regulation** | SOLAS 1974, as amended |
| **Used with** | MSC-30703001 / MSC-30703004 SCBA sets |
| **Alternate thread** | MCY-20304049 — G5/8 |
| **Cylinder valve** | Listed separately: MCV-11401504 (M22×1.5) / MCV-11401505 (G5/8) |

TPED | SOLAS 1974 | 300 BAR | 6 L

Genuine OEM equivalent available on request. Confirm neck thread (M22×1.5 or G5/8) and whether a valve is required before ordering. Cylinder markings include charging pressure, capacity and inspection stamp. Illustration for reference; appearance may vary.