P/N MPR-20304050

SCBA Pressure Reducer Unit – M22×1.5

Reductor de presión para ERA – conexión M22×1.5

First-stage pressure reducer for 300 bar positive-pressure SCBA sets. Reduces cylinder pressure to a stable medium pressure for the demand valve, with a built-in medium-pressure safety valve and a low-pressure warning whistle. Hand-wheel connection to the cylinder valve, thread M22×1.5 (G5/8 version available).

KEY FEATURES

- Reduces 300 bar cylinder pressure to medium pressure for the demand valve
- Built-in medium-pressure safety valve
- Low-pressure warning whistle signals remaining-air reserve
- Lines to the pressure gauge (high pressure) and demand valve (medium pressure)
- Spare / replacement part for the 300 bar SCBA range

PRODUCT



TECHNICAL SPECIFICATIONS

Part number	MPR-20304050
Type	SCBA first-stage pressure reducer
Cylinder connection	M22×1.5
Max. inlet pressure	30 MPa (300 bar) Per OEM user manual
Outlet pressure	0.7 ± 0.05 MPa Per OEM user manual
Safety valve opening	1.1 ± 0.2 MPa Per OEM user manual
Warning whistle	Sounds at 5.5 ± 0.5 MPa cylinder pressure; 90 dB Per OEM user manual
Used with	MSC-30703xxx / MSC-30705xxx SCBA sets
Alternate thread	MPR-20304051 — G5/8

SCBA SPARE PART | 300 BAR INLET | M22×1.5

Genuine OEM equivalent available on request. Confirm cylinder thread (M22×1.5 or G5/8) and SCBA set in service before ordering. Maintenance by trained, authorised personnel only. Illustration for reference; appearance may vary.