P/N MSC-30703004

Self-Contained Breathing Apparatus – 6 L Alloy Steel, 300 bar

Equipo de respiración autónoma (ERA) – cilindro de acero 6 L

Positive-pressure, self-contained compressed-air breathing apparatus (SCBA) for the shipboard fire-fighter's outfit required by SOLAS. Complete set with full face mask, air supply (demand) valve, pressure reducer, pressure gauge with remaining-air warning, backboard with harness and a 6 L alloy-steel cylinder charged to 300 bar.

KEY FEATURES

- 6 L alloy-steel cylinder — 1,800 L of stored air at 300 bar
- Rated duration 50–60 min; set weight ≤ 16 kg
- Positive-pressure full face mask (EN 136 Class 2) with air supply valve
- Sound-and-light remaining-air alarm with pressure gauge
- Backboard and adjustable harness for hands-free wear
- Interchangeable 300 bar cylinders across the range

PRODUCT



TECHNICAL SPECIFICATIONS

Part number	MSC-30703004
Type	Positive-pressure, open-circuit compressed-air SCBA
Cylinder	Alloy steel, 6 L
Working pressure	300 bar
Air stored	1,800 L
Rated duration	50–60 min
Weight	≤ 16 kg
Warning device	Sound-light alarm + pressure gauge
Components	Full face mask, air supply valve, pressure reducer, pressure gauge, backboard & harness, cylinder
Standards	SOLAS 74 Reg. II-2/10 & X/3; FSS Code Ch. 3; IMO MSC.1/Circ.1499; ISO 23269-2:2011
Approval	EU MED (wheel mark), MED/3.7 — DNV type examination
Variants	MSC-30703001 (CCS-approved version) MSC-30703026 / -30703024 (audible-alarm version, MED / CCS)
Limitations	Approved as the breathing apparatus of a fire-fighter's outfit; not for use in accidents with cargoes; to be used with an approved fireproof lifeline

DNV MED / 3.7 | SOLAS II-2/10 | FSS CODE CH. 3 | ISO 23269-2:2011 | 300 BAR

Genuine OEM equivalent available on request. Spare cylinders: MCY-20304040 (M22×1.5) / MCY-20304049 (G5/8). Illustration for reference; appearance may vary.

www.mantto.com
sales@mantto.com
+1 956 627 1082